



## RF Exposure Evaluation Declaration

---

**FCC ID:** TK4WPJ428

**APPLICANT:** Compex Systems Pte Ltd

**Application Type:** Class II Permissible Change

**Product:** Wireless Access Point

**Model No.:** WPJ428HV

**Serial Model:** WPJ428LV, WPJ418LV, WPJ418HV, MMS428LV,  
MMS428HV, MMS418LV, MMS418HV

**Trademark:** COMPEX

**FCC Classification:** Digital Transmission System (DTS)  
Unlicensed National Information Infrastructure (UNII)

Reviewed By : *Jame Yuan*

( Jame Yuan )

Approved By : *Marlin Chen*

( Marlin Chen )



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

## Revision History

Report No.	Version	Description	Issue Date	Note
1704RSU00207	Rev. 01	Initial report	06-25-2017	Valid

## 1. PRODUCT INFORMATION

### 1.1. Equipment Description

Product Name	Wireless Access Point
Model No.	WPJ428HV
Serial Model:	WPJ428LV, WPJ418LV, WPJ418HV, MMS428LV, MMS428HV, MMS418LV, MMS418HV
Brand Name	COMPEX
Wi-Fi Specification	802.11a/b/g/n/ac
Frequency Range	<b><u>2.4GHz:</u></b> For 802.11b/g/n-HT20: 2412 ~ 2462 MHz For 802.11n-HT40: 2422 ~ 2452 MHz <b><u>5GHz:</u></b> For 802.11a/n-HT20/ ac-VHT20: 5180~5320MHz, 5500~5720MHz, 5745~5825MHz For 802.11n-HT40/ac-VHT40: 5190~5310MHz, 5510~5710MHz, 5755~5795MHz For 802.11ac-VHT80: 5210MHz, 5290MHz, 5530MHz, 5610MHz, 5690MHz, 5775MHz
Type of Modulation	802.11b: DSSS 802.11g/a/n/ac: OFDM

## 1.2. Antenna Description

Antenna Type	Frequency Band (MHz)	TX Paths	Per Chain Max Antenna Gain (dBi)	
			Ant 0	Ant 1
Panel Antenna 1#	2412 ~ 2462	1	11	--
		2	11	11
Panel Antenna 2#	5150 ~ 5250, 5745 ~ 5785	1	25	--
		2	25	25
Panel Antenna 3#	2412 ~ 2462	1	8	--
		2	8	8
	5180 ~ 5825	1	10	--
		2	10	10

Note 1: The device didn't support beam-forming technology and Cyclic Delay Diversity (CDD) technology, and the transmit signals are uncorrected, so no add array gain to the band power and band PSD.

Note 2: For SISO mode, only the Ant 0 chain can transmit. 11a&11b&11g mode support SISO mode, 11n mode support MIMO mode.

Note 3: When the device working on UNII-2A & UNII-2C bands, only the panel antenna 3# or antenna gain less than 10dBi can be used.

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

r = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	Wireless Access Point
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to clause 1.2.

### For 2.4GHz ISM Band:

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density Limit (mW/cm <sup>2</sup> )	Safety Distance R (cm)
802.11b/g /n-HT20/n-HT40	2412 ~ 2462	22.94	1	14.04

### For 5GHz UNII Band:

Test Mode	Frequency Band (MHz)	Maximum Average Output Power (dBm)	Power Density Limit (mW/cm <sup>2</sup> )	Safety Distance R (cm)
802.11a/n/ac	5180 ~ 5240	14.89	1	27.85
	5260 ~ 5320	19.48	1	8.40
	5500 ~ 5720	19.52	1	8.44
	5745 ~ 5825	19.32	1	46.39

### CONCULISON:

Both of the WLAN 2.4GHz Band and WLAN 5GHz Band can transmit simultaneously. Therefore, the Min Safety Distance R = 14.04cm + 46.39cm = 60.43cm.

\_\_\_\_\_ The End \_\_\_\_\_